

Pro Strip Heavy Duty Floor Stripper

Version Number: 2 Preparation date: 2015-07-24

1. IDENTIFICATION

Product name:Pro Strip Heavy Duty Floor StripperProduct Code:95032351, 95032360, 95117700

SDS #: MS0800160

Recommended use: • Industrial/Institutional

Floor stripper

 This product is intended to be diluted prior to use Uses other than those identified are not recommended

Manufacturer, importer, supplier:Canadian HeadquartersSealed Air - CanadaUS Headquarters3755 Laird Road

Diversey, Inc. 8310 16th St.

Uses advised against:

Sturtevant, Wisconsin 53177-1964

Phone: 1-888-352-2249

MSDS Internet Address: www.diversey.com

Emergency telephone number: 1-800-851-7145 (U.S.); 1-651-917-6133 (Int'l)

2. HAZARDS IDENTIFICATION

Mississauga, Ontario L5L 0B3

Phone: 1-800-668-7171

Classification for the undiluted product

Skin corrosion/irritation
Serious eye damage/eye irritation
Specific target organ toxicity (single exposure)
Metal Corrosion:

Category 1
Category 3
Category 1



Signal Word: Danger.

Precautionary Statements

CAUSES SEVERE SKIN BURNS AND SERIOUS EYE DAMAGE. MAY CAUSE RESPIRATORY IRRITATION. MAY BE CORROSIVE TO METALS.

Avoid contact with eyes, skin and clothing. Causes burns/ serious damage to mouth, throat and stomach. Keep only in original container. Do not breathe vapors. Wash affected areas thoroughly after handling. Use only in a well-ventilated area. Wear chemical-splash goggles, chemical-resistant gloves and protective footwear. IF SWALLOWED: Rinse mouth. DO NOT induce vomiting unless directed to do so by medical personnel. Drink a cupful of milk or water. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water for at least 15 minutes. Wash contaminated clothing before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. Immediately call a Poison Center (1-800-851-7145) or physician. Absorb spillage to prevent material damage. Store in a well-ventilated place. Keep

Pro Strip Heavy Duty Floor Stripper

1 of 6



container tightly closed. Store in corrosive-resistant container with a resistant inner liner. Dispose of in accordance with all federal, state and local applicable regulations. SUPPLEMENTAL INFORMATION:. Mix only with water. DO NOT MIX WITH ANY OTHER PRODUCT OR CHEMICAL. Can react to release hazardous gases. May vigorously react with acids resulting in spattering and excessive heat.

Health hazards not otherwise classified (HHNOC) - Not applicable Physical hazards not otherwise classified (PHNOC) - Not applicable

Classification for the diluted product @ 1:4

Skin corrosion/irritation Category 2
Serious eye damage/eye irritation Category 1



Dilution Signal word:

Danger.

Precautionary Statements

CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE DAMAGE.

Avoid contact with eyes, skin and clothing. Causes burns/ serious damage to mouth, throat and stomach. Keep container tightly closed. Wash affected areas thoroughly after handling. Wear chemical-splash goggles and chemical-resistant gloves. IF SWALLOWED: Rinse mouth. DO NOT induce vomiting unless directed to do so by medical personnel. Drink a cupful of milk or water. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. Immediately call a Poison Center (1-800-851-7145) or physician. Dispose of in accordance with all federal, state and local applicable regulations. SUPPLEMENTAL INFORMATION:. Mix only with water. DO NOT MIX WITH ANY OTHER PRODUCT OR CHEMICAL. Can react to release hazardous gases. May vigorously react with acids resulting in spattering and excessive heat.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Classified Ingredients

Ingredient(s)	CAS#	Weight %
Monoethanolamine	141-43-5	10 - 20%
Benzyl alcohol	100-51-6	5 - 10%
Diethylene glycol monoethyl ether	111-90-0	3% - < 5%
Sodium hydroxide	1310-73-2	3% - < 5%
Sodium xylene sulfonate	1300-72-7	3% - < 5%

^{*}Exact percentages are being withheld as trade secret information

4. FIRST AID MEASURES

Undiluted Product:

Eyes: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes

Skin: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water for at least 15 minutes.

Inhalation: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion: IF SWALLOWED: Rinse mouth. DO NOT induce vomiting unless directed to do so by medical personnel. Drink a cupful of milk or water.

<u>Most Important Symptoms/Effects:</u> No information available.

 $\underline{\textbf{Immediate medical attention and special treatment needed}}. Not applicable.$

Aggravated Medical Conditions: Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may be more susceptible to irritating effects.

Diluted Product:

Eyes: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes.

Skin: IF ON SKIN: Wash with plenty of soap and water If skin irritation occurs: Get medical advice/attention

Inhalation: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion: IF SWALLOWED: Rinse mouth. DO NOT induce vomiting unless directed to do so by medical personnel. Drink a cupful of milk or

water

5. FIRE-FIGHTING MEASURES

Specific methods: No special methods required

Suitable extinguishing media: The product is not flammable. Extinguish fire using agent suitable for surrounding fire.

Specific hazards: Not applicable.

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH

(approved or equivalent) and full protective gear.

Extinguishing media which must not be used for safety reasons: No information available.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Put on appropriate personal protective equipment (see Section 8.).

Environmental precautions Clean-up methods - large spillage. Absorb spill with inert material (e.g. dry sand or earth), then place in

and clean-up methods: a chemical waste container. Use a water rinse for final clean-up.

7. HANDLING AND STORAGE

Handling: Avoid contact with skin, eyes and clothing. Do not taste or swallow. Avoid breathing vapors or mists. Use only with adequate ventilation. Remove and wash contaminated clothing and footwear before re-use. Wash thoroughly after handling. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. Mix only with water. Do not mix with any other product or chemical. Can react to release hazardous gases. May vigorously react with acids resulting in spattering and excessive heat. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.

Storage: Protect from freezing. Keep tightly closed in a dry, cool and well-ventilated place. KEEP OUT OF REACH OF CHILDREN.

Aerosol Level (if applicable): Not applicable

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines:

Ingredient(s)	CAS#	ACGIH	OSHA
Monoethanolamine	141-43-5	6 ppm (STEL) 3 ppm (TWA)	3 ppm (TWA) 6 mg/m³ (TWA)
Benzyl alcohol	100-51-6	-	-
Diethylene glycol monoethyl ether	111-90-0	-	-
Sodium hydroxide	1310-73-2	2 mg/m³ (Ceiling)	2 mg/m³ (TWA)
Sodium xylene sulfonate	1300-72-7	-	-

Undiluted Product:

Engineering measures to reduce exposure:

Use only in well-ventilated areas Good general ventilation should be sufficient to control airborne levels Respiratory protection is not required if good ventilation is maintained.

Personal Protective Equipment

Eye protection: Chemical-splash goggles. Hand protection: Chemical-resistant gloves.

Skin and body protection: Protective footwear. If major exposure is possible, wear suitable protective clothing and footwear. Respiratory protection: In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection program

that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever

workplace conditions warrant a respirator's use.

Hygiene measures: Handle in accordance with good industrial hygiene and safety practice.

Diluted Product:

Engineering measures to reduce exposure: No special ventilation requirements General room ventilation is adequate

Personal Protective Equipment

Eye protection: Chemical-splash goggles. **Hand protection:** Chemical-resistant gloves.

Skin and body protection:
Respiratory protection:
No personal protective equipment required under normal use conditions.
No personal protective equipment required under normal use conditions.
Hygiene measures:
Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES:

Physical State: Liquid Color: Clear

Evaporation Rate: No information available Odor: Cherry Almond

Odor threshold: No information available. Boiling point/range: Not determined

Melting point/range: Not determined Decomposition temperature: Not determined

Autoignition temperature: No information available Solubility: Completely Soluble

Solubility in other solvents: No information available Relative Density (relative to water): 1.06 Density: 8.84 lbs/gal 1.06 Kg/L Vapor density: No information available Bulk density: No information available Vapor pressure: No information available.

Flash point: $> 200 \, ^{\circ}\text{F} \, > \, 93.3 \, ^{\circ}\text{C}$ Dilution Flash Point: $200 \, ^{\circ}\text{F} \, 93.3 \, ^{\circ}\text{C}$ Partition coefficient (n-octanol/water): No information available

Viscosity: No information available

Elemental Phosphorus: 0.00 % by wt. VOC: 12.3 % *

VOC % by wt. at use dilution 2.46 % * **pH**: 13 **Dilution pH:** 13 @ 1:4 Flammability (Solid or Gas): Not applicable

Metal Corrosion: Not determined

Explosion limits: - upper: Not determined - lower: Not determined

* - Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Consumer Products, Sections 94508

10. STABILITY AND REACTIVITY

Reactivity: Not Applicable Stability: The product is stable

Possibility of hazardous reactions: May vigorously react with acids resulting in spattering and excessive heat.

Hazardous decomposition products: None reasonably foreseeable.

Materials to avoid: Strong acids. Do not mix with any other product or chemical unless specified in the use directions.

Conditions to avoid: Do not mix with any other product or chemical.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Eye contact, Skin contact, Inhalation, Ingestion

Delayed, immediate, or chronic effects and symptoms from short and long-term exposure

Skin contact: Corrosive. Causes severe burns. Symptoms may include burns, blisters, redness and pain (which may be delayed). Eye contact: Corrosive. Causes serious eye damage. Symptoms may include pain, burning sensation, redness, watering, blurred vision or loss of vision.

Ingestion: Causes burns/ serious damage to mouth, throat and stomach. Symptoms may include stomach pain and nausea. Inhalation: May cause irritation and corrosive effects to nose, throat and respiratory tract. Symptoms may include coughing and

difficulty breathing.

Sensitization: No known effects. Target Organs (SE): None known Target Organs (RE): None known

Numerical measures of toxicity

ATE - Oral (mg/kg): >5000 ATE - Dermal (mg/kg): >5000 ATE - Inhalatory, mists (mg/l): 12 ATE - Inhalatory, vapors (mg/l): >50

12. ECOLOGICAL INFORMATION

Ecotoxicity: No information available.

Persistence and Degradability: No information available.

Bioaccumulation: No information available.

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products: This product, as sold, if discarded or disposed, is a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Dispose in compliance with all Federal, state, provincial, and local laws and regulations. This product, when diluted as stated on this SDS, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the waste solution meets RCRA criteria for hazardous waste. Dispose in compliance with all Federal, state, provincial, and local laws and regulations.

Contaminated Packaging: Do not re-use empty containers.

RCRA Hazard Class (undiluted product): D002 Corrosive Waste

RCRA Hazard Class (diluted product): Not Regulated

14. TRANSPORT INFORMATION

<u>DOT/TDG/IMDG:</u> Proper shipping descriptions can vary by pack size. Please refer to the Diversey HazMat Library, **only available through** Internet Explorer, http://naextranet.diversey.com/dot/, for up to date shipping information.

DOT (Ground) Bill of Lading Description: UN3267, CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S., (ethanolamine, sodium hydroxide), 8, II

IMDG (Ocean) Bill of Lading Description: UN3267, CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S., (ethanolamine, sodium hydroxide), 8, II

15. REGULATORY INFORMATION

International Inventories at CAS# Level

All components of this product are listed on the following inventories: U.S.A. (TSCA), Canada (DSL/NDSL).

U.S. Regulations

California Proposition 65: This product is not subject to the reporting requirements under California's Proposition 65.

RIGHT TO KNOW (RTK)

Ingredient(s)	CAS#	MARTK:	NJRTK:	PARTK:	RIRTK:
Water	7732-18-5	=	•	ı	=
Monoethanolamine	141-43-5	X	X	X	=
Benzyl alcohol	100-51-6	X	=	X	=
Diethylene glycol monoethyl ether	111-90-0	-	X	-	=
Sodium hydroxide	1310-73-2	X	X	X	X
Sodium xylene sulfonate	1300-72-7	-	-	-	-

CERCLA/ SARA

Ingredient(s)	CAS#	Weight %	CERCLA/SARA RQ (lbs)	Section 302 TPQ (lbs)	Section 313
Diethylene glycol monoethyl ether	111-90-0	3% - < 5%			Χ
Sodium hydroxide	1310-73-2	3% - < 5%	1000		

Ingredient(s)	CAA HAP	CAA ODS	CWA Priority Pollutants
Diethylene glycol monoethyl ether	X		

SARA 311/312 Hazard Categories

Immediate: X
Delayed: Fire: Reactivity: Sudden Release of Pressure: -

Canadian Regulations

16. OTHER INFORMATION

NFPA (National Fire Protection Association)

Rating Scale: (Low Hazard) 0 - 4 (Extreme Hazard)

Health 3 Flammability 0 Instability 0

Version Number: 2

Preparation date: 2015-07-24

Reason for revision:
Prepared by:

Not applicable
NAPRAC

Additional advice: • Does not contain an added fragrance

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.