# SAFETY DATA SHEET



Oven & Grill Cleaner

### Section 1. Identification

GHS product identifier : Oven & Grill Cleaner

Product code : 055

Other means of identification

: Not available.

Product type : Aerosol.

For Industrial and Institutional Use Only

#### Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Oven, Fryer, Grill Cleaner	
Uses advised against	Reason

Supplier's details : Betco Corporation

400 Van Camp Road

Bowling Green, Ohio 43402

www.betco.com 888-462-3826

Emergency telephone number (with hours of operation)

: Chemtrec (800) 424-9300

24 hour

## Section 2. Hazards identification

**OSHA/HCS status** 

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

: FLAMMABLE AEROSOLS - Category 1
GASES UNDER PRESSURE - Compressed gas
SKIN CORROSION - Category 1A

SKIN CORROSION - Category 1A SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1

**GHS** label elements

Hazard pictograms :









Signal word : Danger

**Hazard statements** : Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

**Precautionary statements** 

### Section 2. Hazards identification

#### **Prevention**

: Wear protective gloves. Wear eye or face protection: Recommended: splash goggles. Wear protective clothing: Recommended: Chemical resistant gloves. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not breathe dust or mist. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Pressurized container: Do not pierce or burn, even after use.

#### Response

: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or physician. IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or physician. IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.

#### **Storage**

: Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place.

#### **Disposal**

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards not otherwise classified

: None known.

### Section 3. Composition/information on ingredients

Substance/mixture

Mixture

Other means of identification

: Not available.

Ingredient name	%	CAS number
sodium hydroxide	≤10	1310-73-2
2-(2-butoxyethoxy)ethanol	≤5	112-34-5
propane	≤5	74-98-6
2,2',2"-nitrilotriethanol	≤5	102-71-6
Surfactant	≤3	proprietary
Poly(oxy-1,2-ethanediyl), α-undecyl-ω-hydroxy-, branched and linear	≤3	127036-24-2
D-gluconic acid	≤3	526-95-4
sodium dodecylbenzenesulfonate	≤3	25155-30-0
(R)-p-mentha-1,8-diene	≤1	5989-27-5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### **Description of necessary first aid measures**

**Eye contact** 

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Date of issue/Date of revision: 8/25/2020Date of previous issue: No previous validationVersion: 12/16

### Section 4. First aid measures

#### **Inhalation**

: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

#### **Skin contact**

: Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

#### Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : Causes serious eye damage.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: Causes severe burns. May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

pain watering redness

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion : Adverse symptoms may include the following:

stomach pains

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments**: No specific treatment.

Date of issue/Date of revision: 8/25/2020Date of previous issue: No previous validationVersion: 13/16

### Section 4. First aid measures

#### Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

#### **Extinguishing media**

media

Suitable extinguishing media

Unsuitable extinguishing

: Use an extinguishing agent suitable for the surrounding fire.

: None known.

# Specific hazards arising from the chemical

: Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

# Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon dioxide

carbon monoxide nitrogen oxides sulfur oxides metal oxide/oxides

# Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

# Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

#### For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

#### **Environmental precautions**

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Date of issue/Date of revision: 8/25/2020Date of previous issue: No previous validationVersion: 14/16

### Section 6. Accidental release measures

#### Methods and materials for containment and cleaning up

#### Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

#### Large spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible. absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

#### **Precautions for safe handling**

#### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

#### Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### Occupational exposure limits

Ingredient name	Exposure limits
sodium hydroxide	ACGIH TLV (United States, 3/2017).  C: 2 mg/m³  OSHA PEL 1989 (United States, 3/1989).  CEIL: 2 mg/m³  NIOSH REL (United States, 10/2016).  CEIL: 2 mg/m³  OSHA PEL (United States, 6/2016).  TWA: 2 mg/m³ 8 hours.
2-(2-butoxyethoxy)ethanol	ACGIH TLV (United States, 3/2018). TWA: 10 ppm 8 hours. Form: Inhalable fraction and vapor

Date of issue/Date of revision : 8/25/2020 Date of previous issue Version: 1 5/16 : No previous validation

### Section 8. Exposure controls/personal protection

OSHA PEL 1989 (United States, 3/1989). propane

> TWA: 1000 ppm 8 hours. TWA: 1800 mg/m<sup>3</sup> 8 hours.

NIOSH REL (United States, 10/2016).

TWA: 1000 ppm 10 hours. TWA: 1800 mg/m<sup>3</sup> 10 hours. OSHA PEL (United States, 5/2018).

TWA: 1000 ppm 8 hours. TWA: 1800 mg/m<sup>3</sup> 8 hours.

ACGIH TLV (United States, 3/2018). Oxygen Depletion [Asphyxiant]. Explosive potential.

2,2',2"-nitrilotriethanol ACGIH TLV (United States, 3/2018).

TWA: 5 mg/m<sup>3</sup> 8 hours.

None. None. None. None.

AIHA WEEL (United States, 7/2018).

TWA: 30 ppm 8 hours.

Surfactant

Poly(oxy-1,2-ethanediyl), α-undecyl-ω-hydroxy-, branched and linear

D-gluconic acid

sodium dodecylbenzenesulfonate

(R)-p-mentha-1,8-diene

#### **Appropriate engineering** controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

#### **Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/ or face shield. If inhalation hazards exist, a full-face respirator may be required instead. Recommended: splash goggles

### Skin protection **Hand protection**

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Date of issue/Date of revision : 8/25/2020 Date of previous issue Version :1 6/16 : No previous validation

## Section 8. Exposure controls/personal protection

**Body protection** 

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Recommended: Chemical resistant gloves

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Personal protective equipment (Pictograms)



## Section 9. Physical and chemical properties

**Appearance** 

Physical state : Gas. [Compressed gas.]

Color : Beige.
Odor : Fruity.

Odor threshold : Not available.

**pH** : 14

Melting point: Not available.Boiling point: Not available.Flash point: Not available.Evaporation rate: Not available.Flammability (solid, gas): Not available.Lower and upper explosive: Not available.

(flammable) limits

Vapor pressure : 5.3 to 8 kPa (40 to 60 mm Hg) [room temperature]

: Not available.

Vapor density : Not available.

Relative density : Not available.

**Solubility** : Easily soluble in the following materials: cold water and hot water.

Solubility in water : Not available.

Partition coefficient: noctanol/water : Not available.

Auto-ignition temperature: Not available.Decomposition temperature: Not available.Viscosity: Not available.

Flow time (ISO 2431)
Aerosol product

Type of aerosol : Spray
Heat of combustion : 4.438 kJ/g

Date of issue/Date of revision: 8/25/2020Date of previous issue: No previous validationVersion: 17/16

# Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : Avoid all possible sources of ignition (spark or flame).

**Incompatible materials**: Not available.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# **Section 11. Toxicological information**

#### Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
2-(2-butoxyethoxy)ethanol	LD50 Dermal	Rabbit	2700 mg/kg	-
	LD50 Oral	Rat	4500 mg/kg	-
2,2',2"-nitrilotriethanol	LD50 Oral	Rat	7.39 g/kg	-
sodium dodecylbenzenesulfonate	LD50 Oral	Rat	438 mg/kg	-
(R)-p-mentha-1,8-diene	LD50 Dermal LD50 Oral	Rabbit Rat	>5000 mg/kg 4400 mg/kg	-

#### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
sodium hydroxide	Eyes - Severe irritant	Monkey	-	24 hours 1	-
				Percent	
	Eyes - Mild irritant	Rabbit	-	400	-
				Micrograms	
	Eyes - Severe irritant	Rabbit	-	24 hours 50	-
				Micrograms	
	Eyes - Severe irritant	Rabbit	-	1 Percent	-
	Eyes - Severe irritant	Rabbit	-	0.5 minutes 1	-
				milligrams	
	Skin - Mild irritant	Human	-	24 hours 2	-
				Percent	
	Skin - Severe irritant	Rabbit	-	24 hours 500	-
				milligrams	
2-(2-butoxyethoxy)ethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 20	-
				milligrams	
	Eyes - Severe irritant	Rabbit	-	20 milligrams	-
2,2',2"-nitrilotriethanol	Eyes - Mild irritant	Rabbit	-	10 milligrams	-
	Eyes - Severe irritant	Rabbit	-	20 milligrams	-
	Skin - Mild irritant	Human	-	72 hours 15	-
				milligrams	
				Intermittent	
	Skin - Severe irritant	Mouse	-	50 Percent	-
	Skin - Mild irritant	Rabbit	-	24 hours 560	-
				milligrams	
sodium	Eyes - Severe irritant	Rabbit	-	24 hours 250	-
					<u> </u>

Date of issue/Date of revision: 8/25/2020Date of previous issue: No previous validationVersion: 18/16

Oven & Grill Cleaner

# **Section 11. Toxicological information**

dodecylbenzenesulfonate				Micrograms	
	Eyes - Severe irritant	Rabbit	-	1 Percent	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20	-
				milligrams	
(R)-p-mentha-1,8-diene	Skin - Mild irritant	Rabbit	-	24 hours 10	-
				Percent	

#### **Sensitization**

Not available.

#### **Mutagenicity**

Not available.

#### Carcinogenicity

Not available.

#### Classification

Product/ingredient name	OSHA	IARC	NTP
2,2',2"-nitrilotriethanol	-	3	-
(R)-p-mentha-1,8-diene	-	3	-

#### Reproductive toxicity

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Name	• •	Route of exposure	Target organs
propane	Category 3	Not applicable.	Respiratory tract irritation
2,2',2"-nitrilotriethanol	Category 3	Not applicable.	Respiratory tract irritation

### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

Information on the likely routes of exposure

: Routes of entry anticipated: Oral, Dermal, Inhalation.

#### Potential acute health effects

**Eye contact** : Causes serious eye damage.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: Causes severe burns. May cause an allergic skin reaction.

**Ingestion**: No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact**: Adverse symptoms may include the following:

pain watering redness

Date of issue/Date of revision: 8/25/2020Date of previous issue: No previous validationVersion: 19/16

# **Section 11. Toxicological information**

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

**Ingestion** : Adverse symptoms may include the following:

stomach pains

#### Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

**Potential immediate** 

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

**Potential immediate** 

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to

: No known significant effects or critical hazards.

very low levels.

Carcinogenicity: No known significant effects or critical hazards.Mutagenicity: No known significant effects or critical hazards.Teratogenicity: No known significant effects or critical hazards.Developmental effects: No known significant effects or critical hazards.

**Numerical measures of toxicity** 

**Acute toxicity estimates** 

Not available.

**Fertility effects** 

# **Section 12. Ecological information**

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
sodium hydroxide	Acute EC50 40.38 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 125 ppm Fresh water	Fish - Gambusia affinis - Adult	96 hours
2-(2-butoxyethoxy)ethanol	Acute LC50 1300000 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
2,2',2"-nitrilotriethanol	Acute EC50 609.98 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 11800000 μg/l Fresh water Chronic NOEC 16000 μg/l Fresh water	Fish - Pimephales promelas Daphnia - Daphnia magna	96 hours 21 days
sodium dodecylbenzenesulfonate	Acute EC50 29000 μg/l Fresh water	Algae - Chlorella pyrenoidosa - Exponential growth phase	96 hours
•	Acute EC50 7.81 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
Date of issue/Date of revision	: 8/25/2020 Pate of provious issue	: No previous validation Version	1 10/16

Date of issue/Date of revision : 8/25/2020 Date of previous issue : No previous validation Version : 1 10/16

# Section 12. Ecological information

	•		
	Acute EC50 0.15 ppm Fresh water	Daphnia - Daphnia pulex	48 hours
	Acute IC50 112.4 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata - Exponential growth phase	72 hours
(R)-p-mentha-1,8-diene	Acute LC50 1.18 ppm Fresh water Acute EC50 421 µg/l Fresh water Acute EC50 688 µg/l Fresh water	Fish - Lepomis macrochirus Daphnia - Daphnia magna Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling)	96 hours 48 hours 96 hours

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
2-(2-butoxyethoxy)ethanol propane	1 1.09	-	low low
2,2',2"-nitrilotriethanol	-1	<3.9	low
sodium dodecylbenzenesulfonate	1.96	-	low
(R)-p-mentha-1,8-diene	4.38	-	high

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

## Section 13. Disposal considerations

#### **Disposal methods**

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

# **Section 14. Transport information**

	DOT Classification	TDG Classification	Mexico Classification	ADR/RID	IMDG	IATA
UN number	UN1950	Not available.	UN1950	UN1950	UN1950	UN1950
UN proper shipping name	Aerosols, Flammable, Corrosive	Product Not Available	Aerosols, Flammable, Corrosive	Aerosols, Flammable, Corrosive	AEROSOLS	AEROSOLS

Date of issue/Date of revision : 8/25/2020 Date of previous issue : No previous validation Version : 1 11/16

# **Section 14. Transport information**

Transport hazard class(es)	2.1 (8)	2.1	2.1	2	2.1 (8)	2.1 (8)
Packing group	-	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.	No.

#### **Additional information**

**DOT Classification** : Reportable quantity 20000 lbs / 9080 kg. Package sizes shipped in quantities less

than the product reportable quantity are not subject to the RQ (reportable quantity)

transportation requirements.

Limited quantity Yes.

**TDG Classification** : Product classified as per the following sections of the Transportation of Dangerous

Goods Regulations: 2.13-2.17 (Class 2).

: Tunnel code (D) ADR/RID

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in the

event of an accident or spillage.

Transport in bulk according to Annex II of MARPOL and

the IBC Code

: Not available.

# Section 15. Regulatory information

**U.S. Federal regulations** : TSCA 8(a) CDR Exempt/Partial exemption: Not determined

Commerce control list precursor: 2,2',2"-nitrilotriethanol

Clean Water Act (CWA) 311: sodium hydroxide; sodium dodecylbenzenesulfonate Clean Air Act (CAA) 112 regulated flammable substances: propane; butane

Clean Air Act Section 112

(b) Hazardous Air **Pollutants (HAPs)**  : Listed

Clean Air Act Section 602

: Not listed

Class I Substances

: Not listed

Clean Air Act Section 602 **Class II Substances** 

**DEA List I Chemicals** 

: Not listed

(Precursor Chemicals)

: Not listed

**DEA List II Chemicals** (Essential Chemicals)

#### **SARA 302/304**

**Composition/information on ingredients** 

No products were found.

**SARA 304 RQ** : Not applicable.

Date of issue/Date of revision : 8/25/2020 12/16 Date of previous issue : No previous validation Version: 1

# **Section 15. Regulatory information**

#### **SARA 311/312**

Classification

: FLAMMABLE AEROSOLS - Category 1

GASES UNDER PRESSURE - Compressed gas

SKIN CORROSION - Category 1A SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1

#### Composition/information on ingredients

Name	%	Classification
sodium hydroxide	≤10	CORROSIVE TO METALS - Category 1
		SKIN CORROSION - Category 1A
		SERIOUS EYE DAMAGE - Category 1
butane	≤5	FLAMMABLE GASES - Category 1
		GASES UNDER PRESSURE - Liquefied gas
2-(2-butoxyethoxy)ethanol	≤5	EYE IRRITATION - Category 2A
propane	≤5	FLAMMABLE GASES - Category 1
		GASES UNDER PRESSURE - Liquefied gas
		SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)
		(Respiratory tract irritation) - Category 3
2,2',2"-nitrilotriethanol	≤5	SKIN IRRITATION - Category 2
		EYE IRRITATION - Category 2A
		SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)
		(Respiratory tract irritation) - Category 3
Surfactant	≤3	SKIN IRRITATION - Category 2
		EYE IRRITATION - Category 2A
Poly(oxy-1,2-ethanediyl), α-	≤3	ACUTE TOXICITY (oral) - Category 4
undecyl-ω-hydroxy-, branched		SKIN CORROSION - Category 1
and linear		SERIOUS EYE DAMAGE - Category 1
D-gluconic acid	≤3	SKIN IRRITATION - Category 2
		EYE IRRITATION - Category 2A
sodium	≤3	ACUTE TOXICITY (oral) - Category 4
dodecylbenzenesulfonate		SKIN IRRITATION - Category 2
		EYE IRRITATION - Category 2A
(R)-p-mentha-1,8-diene	≤1	FLAMMABLE LIQUIDS - Category 3
		SKIN IRRITATION - Category 2
		SKIN SENSITIZATION - Category 1

#### **SARA 313**

	Product name	CAS number	%
Form R - Reporting requirements	2-(2-butoxyethoxy)ethanol	112-34-5	≤5
Supplier notification	2-(2-butoxyethoxy)ethanol	112-34-5	≤5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

#### **State regulations**

**Massachusetts** 

: The following components are listed: TRIETHANOLAMINE; PROPANE; BUTANE; SODIUM HYDROXIDE; SODIUM DODECYLBENZENE SULFONATE

**New York** 

: The following components are listed: Sodium hydroxide; Sodium dodecylbenzene sulfonate; Dodecylbenzene sulfonate

**New Jersey** 

: The following components are listed: TRIETHANOLAMINE; ETHANOL, 2,2',2"-NITRILOTRIS-; PROPANE; PROPYLENE GLYCOL; 1,2-PROPANEDIOL; GLYCOL

ETHERS; BUTANE; SODIUM HYDROXIDE; CAUSTIC SODA; SODIUM DODECYLBENZENE SULFONATE; BENZENESULFONIC ACID, DODECYL-,

SODIUM SALT

Date of issue/Date of revision: 8/25/2020Date of previous issue: No previous validationVersion: 113/16

Oven & Grill Cleaner

# **Section 15. Regulatory information**

#### **Pennsylvania**

: The following components are listed: ETHANOL, 2,2',2"-NITRILOTRIS-; PROPANE; 1,2-PROPANEDIOL; BUTANE; SODIUM HYDROXIDE; BENZENESULFONIC ACID, DODECYL-, SODIUM SALT

#### California Prop. 65

This product does not require a Safe Harbor warning under California Prop. 65.

#### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Ingredient name	List name	Status
Triethanolamine	Schedule III	Listed

#### **Montreal Protocol**

Not listed.

#### **Stockholm Convention on Persistent Organic Pollutants**

Not listed.

#### **Rotterdam Convention on Prior Informed Consent (PIC)**

Not listed.

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

#### **Inventory list**

Australia : Not determined.
Canada : Not determined.
China : Not determined.
Europe : Not determined.

Japan : Japan inventory (ENCS): Not determined.

Japan inventory (ISHL): Not determined.

: Not determined Malaysia **New Zealand** : Not determined. **Philippines** : Not determined. Republic of Korea : Not determined. **Taiwan** : Not determined. **Thailand** : Not determined. **Turkey**  Not determined. **United States** : Not determined. **Viet Nam** : Not determined.

## **Section 16. Other information**

### **Hazardous Material Information System (U.S.A.)**



### Section 16. Other information

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

#### **National Fire Protection Association (U.S.A.)**



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

#### Procedure used to derive the classification

Classification	Justification
FLAMMABLE AEROSOLS - Category 1	Expert judgment
GASES UNDER PRESSURE - Compressed gas	Expert judgment
SKIN CORROSION - Category 1A	Expert judgment
SERIOUS EYE DAMAGE - Category 1	Expert judgment
SKIN SENSITIZATION - Category 1	Expert judgment

#### **History**

Date of printing : 8/25/2020 Date of issue/Date of : 8/25/2020

revision

Date of previous issue : No previous validation

Version :

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

References : Not available.

**▼** Indicates information that has changed from previously issued version.

**Notice to reader** 

Date of issue/Date of revision: 8/25/2020Date of previous issue: No previous validationVersion: 115/16

Oven & Grill Cleaner

### Section 16. Other information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue/Date of revision: 8/25/2020Date of previous issue: No previous validationVersion: 116/16