



MATERIAL SAFETY DATA SHEET

(Essentially Similar to Form OSHA-174 / 29 CFR 1910-1200)

PRODUCT NAME **InstantFOAM™ alcohol hand sanitizer**
FORMULA AFS6510
HMIS RATING HEALTH = 0 FIRE = 3 REACTIVITY = 0 (Scale 0-4, where 4 = severe hazard)

SECTION I – MANUFACTURER INFORMATION

MANUFACTURED BY DEB FOR	Deb USA, Inc. 1100 Highway 27 South Stanley, NC 28164	EMERGENCY CONTACT	Chemtrec 800-424-9300 (24 hour)
PHONE NUMBER	704-263-4240	PREPARED BY	Chemist
		REVISION DATE	March 1, 2010

SECTION II – INGREDIENTS

This product is manufactured and labeled in compliance with the Federal Food, Drug, and Cosmetic Act, and is exempt from the labeling requirements of the OSHA Hazard Communication Standard. All product ingredients are listed below.

<u>ACTIVE INGREDIENT</u>	<u>CAS NUMBER</u>	<u>FORMULA, %</u>
Ethyl Alcohol	64-17-5	72 v/v

INACTIVE INGREDIENTS

Water	7732-18-5
n-Propanol	71-23-8
Coco-Glucoside	141464-42-8
Glyceryl Oleate	68424-61-3
PEG-7 Glyceryl Cocoate	68201-46-7
PEG-200 Hydrogenated Glyceryl Palmate	67784-88-7
Dihydroxypropyl PEG-5 Linoleammonium Chloride	168677-75-6
Behentrimonium Chloride	17301-53-0
Bis-PEG-12 Dimethicone	102783-01-7

Data marked with asterisk (*) in section III below refer to the properties of Ethyl Alcohol

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT	NA	SPECIFIC GRAVITY (H ₂ O = 1)	0.80
VAPOR PRESSURE (mmHg)	ND	MELTING POINT	NA
VAPOR DENSITY (Air = 1)	ND	EVAPORATION RATE (Butyl Acetate = 1)	1.4 *
SOLUBILITY IN WATER	Complete	pH	NA
APPEARANCE & ODOR	Clear to slightly opaque liquid with an alcohol odor		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method Used)	72°F (ASTM D1310 open cup) 72°F (ASTM D56-02 closed cup)
FLAMMABLE LIMITS	LEL: ND UEL: ND
EXTINGUISHING MEDIA	Dry chemical, carbon dioxide, water spray (fog) or alcohol foam
SPECIAL FIRE FIGHTING PROCEDURES	Blanket fire with extinguishing medium.
UNUSUAL FIRE AND EXPLOSION HAZARDS	Undetermined

MATERIAL SAFETY DATA SHEET – InstantFOAM™ alcohol hand sanitizer, page 2

SECTION V - REACTIVITY DATA

STABILITY	Unstable Stable	X	Conditions to Avoid:	Heat or ignition sources
INCOMPATIBILITY	Oxidizing agents; may react with aluminum at high temperatures			
HAZARDOUS DECOMPOSITION OR BY-PRODUCTS	Ammonia, nitrous oxides, and hydrogen chloride are produced upon combustion.			
HAZARDOUS POLYMERIZATION	May Occur Will not Occur	X	Conditions to Avoid:	None known

SECTION VI – HEALTH HAZARD DATA

ROUTE(S) OF ENTRY Inhalation, Ingestion only by accidental or intentional misuse

HEALTH HAZARDS

Skin:	Excessive exposure may cause irritation or dryness.
Eyes:	May cause temporary irritation.
Ingestion:	May result in vomiting.
Inhalation:	Vapors may cause drowsiness.

EMERGENCY AND FIRST AID PROCEDURES

Skin:	Rinse affected area with water. Consult with a physician if irritation persists.
Eyes:	Immediately flush eyes with clean water for at least 15 minutes or until irritation subsides. Consult with a physician if pain or irritation persists.
Ingestion:	Do not induce vomiting. Consult with a physician immediately.
Inhalation:	Remove from exposure. Consult with a physician if condition persists.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

IN CASE OF RELEASE OR SPILL	Apply absorbent material and place in covered containers for disposal.
WASTE DISPOSAL METHOD	Dispose in accordance with state, local and federal regulations.
PRECAUTIONS FOR HANDLING AND STORAGE	Keep out of reach of children and other persons who may misuse the product. Avoid contact with excessive heat, ignition sources, and incompatible materials. Store in cool, well-ventilated area. Do not store in aluminum containers.

SECTION VIII - CONTROL MEASURES

SPECIAL RESPIRATORY PROTECTION	None required
SPECIAL SKIN PROTECTION	None required
SPECIAL EYE PROTECTION	Avoid eye contact.

REVISION HISTORY

Added Flash point (closed cup). Changed name to Deb USA, Inc. [db 02.04.10].
Corrected "Linoleammonium. [db 03.01.10].

While the information and recommendations set forth herein are believed to be accurate as of the date hereof, Deb USA, Inc. makes no warranty with respect thereto and disclaims all liability from reliance thereon, and responsibility for improper application or misuse of product in any manner whatsoever. Final determination of suitability of any material is the sole responsibility of the user.