MAGNE COTE

NEKOOSA COATED PRODUCTS – FOR OFFSET PRINTING ONLY 100# TEXT WITH MAGNETIC COATING ON REVERSE SIDE					AVERAGE CALIPER- 11.0		
					PRICE PER PACKAGE		
ITEM			SHTS	SHTS	1	4	16
CODE	SIZE	CALIPER	PKG.	CTN.	CTN.	CTN.	CTN.
NEK100	8.5 X11	11	125	500	52.86	47.30	44.93
NEK102	12 X18	11	100	300	149.18	135.62	124.31
NEK104	12 X18	13	100	300	161.77	149.39	134.81
NO BROKEN PACKAGES							

** DO NOT RUN THROUGH COLOR COPIERS OR LASER PRINTERS – PRODUCT WILL MELT.

** PAPER FEED DIRECTION- GRIPPER EDGE MAKES A DIFFERENCE BECAUSE OF THE POLARITY OF MAGNETS.

**OTHER SIZES AVAILABLE FROM THE MILL IN FULL CARTON QUANTITIES MACNECOTE

www.magnecote.com

HELPFUL HINTS IN PRINTING YOUR MAGNETIC PAPER

Fan Sheets: to help eliminate any sticking between sheets.

Advance several sheets through press: to find any areas magnet may stick. Potential Solution: tape aluminum plate over area (cut plate to fit on feeder on steel registration board).

If you have a double sheet detector: Mechanical double sheet detectors need to be set up for all paper. On some presses the electronic double sheet detector may have to be shut off.

Check blanket type: use of compressible style recommended.

Delivery area: more than usual spray powder recommended. However, make sure area is as clean as possible before printing.

More air on the slow down wheels: will help in the delivery.

Dryers: keep drying temperature under 120* F.

Feeder table wheels: need to be set light to reduce pressure.

Delivery area load: estimate weight limit.

Post printing operations: use smaller stacks if die cutting or trimming. Fan the sheets prior to packing. Take proper pre-press precautions—leave at least 1/8" between cuts.

Or, visit the Printers FAQ section at www.magnecote.com